

# SK-BA2A3F-X

## 2MP Metal Bullet IP Camera



### FEATURES :

- ~ 2MP Network IR Fixed Bullet
- ~ H.265+/H.264 coding
- ~ ICR auto switch, true day / night vision
- ~ 3D DNR, WDR, HLC, BLC, smart IR, etc.
- ~ 10~20m IR night view distance
- ~ DC12V/PoE power supply
- ~ IP 67 ingress protection
- ~ Support three streams
- ~ Support remote monitoring Apps UniApps
- ~ Intelligent analytics
- ~ ONVIF Profile

### SPECIFICATIONS

Camera	Model	SK-BA2A3F-X	
	Images Sensor	1/2.8" 2MP CMOS	
	Illumination	Color	: 0.01 lux @F1.2, AGC ON; 0 lux with IR
		Black	: 0.001 lux @F1.2, AGC ON; 0 lux with IR
	Shutter	1/2s ~ 1 / 100000s	
	Lens	4mm@F1.6,	
	Lens Mout	M12	
Focus	Fixed Lens		
Image	Video Compression	H. 265+	
	Resolution	1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1, 480× 240, CIF	
	Main Stream	50Hz: 1080P/720P(1~25fps)	
	Sub Stream	50Hz: 720P/D1/CIF (1~25fps)	
Functions	Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser	
	Remote Monitoring	UniApps Software / Mobile APP / IE Browser	
	Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission	
	Network Protocol	UDP, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS	
	Interface Protocol	ONVIF	
	Audio Compression	G711A/U	
	Smart Event	Intrusion detection	
Others	PoE	Yes	
	IR Distance	10 ~ 20 m	
	Protection	IP67	
	Power Supply	DC12V/PoE	
	Power Consumption	<4.5W	
	Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F); Humidity: less than 95 % (non-condensing)	
	Dimensions( mm )	102mm*56mm	

### DIMENSIONS:

