

SK-BA5C3F-MS

**5.0MP Full-Color Video & Audio
PoE Network Camera**



FEATURES :

- 5MP Network IR Bullet Camera
- H.265+/H.264 coding
- ICR auto switch, true day / night vision
- 3D DNR, WDR, HLC, BLC, smart IR, etc.
- 10~20m IR night view distance
- Built-in MIC & audio input
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by UniApps apps
- Intelligent analytics
- ONVIF Profile

DIMENSIONS:



SPECIFICATIONS

| | | |
|-----------|---------------------------|---|
| Camera | Model | SK-BA5C3F-MS |
| | Images Sensor | 1/2.8" 5MP CMOS |
| | Illumination | Color : 0.01 lux @F1.2, AGC ON; 0 lux with IR |
| | | Black : 0.001 lux @F1.2, AGC ON; 0 lux with IR |
| Shutter | 1/2s ~ 1 / 100000s | |
| Image | Lens | 4mm@F1.6 |
| | Lens Mout | M12 |
| | Focus | Fixed Lens |
| Image | Video Compression | H. 265+ |
| | Resolution | 5MP (2560 × 1920), 1080P (1920 × 1080), 720P (1280 × 720), D1, 480× 240, CIF |
| | Main Stream Sub Stream | 50Hz: 5 MP/3MP/1080P/720P(1~25fps) 50Hz: 720P/D1/CIF (1~25fps) |
| Functions | Image Settings | ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser |
| | Remote Monitoring | UniApps Software / Mobile APP / IE Browser |
| | Online Connection | Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission |
| | Network Protocol | UDP, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS |
| Others | Interface Protocol | ONVIF |
| | Storage | Network remote storage; micro SD card storage |
| | Smart Event | Line crossing detection and region intrusion detection |
| | PoE | Yes |
| | IR Distance | 10 ~ 20 m |
| | Protection | IP67 |
| | Power Supply | DC12V/PoE |
| | Power Consumption | <4.5W |
| | Operating Environment | - 30 °C ~ 60 °C (-22°F~140°F); Humidity: less than 95 % (non-condensing) |
| | Dimensions(mm) | 170mm*85mm |