

SK-DA2A3F-X

2MP PoE IP Camera



FEATURES :

- ~ 2MP Network IR Fixed Dome
- ~ H.265+/H.264 coding
- ~ ICR auto switch, true day / night vision
- ~ 3D DNR, WDR, HLC, BLC, smart IR, etc.
- ~ 10~20m IR night view distance
- ~ DC12V/PoE power supply
- ~ IP 67 ingress protection
- ~ Support three streams
- ~ Support remote monitoring Apps UniApps
- ~ ONVIF Profile

SPECIFICATIONS

Camera	Model	SK-DA2A3F-X
	Images Sensor	1/2.8" 2MP CMOS
	Illumination	Color : 0.01 lux @F1.2, AGC ON; 0 lux with IR Black : 0.001 lux @F1.2, AGC ON; 0 lux with IR
	Shutter	1/2s ~ 1 / 100000s
	Lens	3.6mm@F1.6,
	Lens Mout	M12
Image	Focus	Fixed Lens
	Video Compression	H. 265+
	Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, 480× 240, CIF
	Main Stream Sub Stream	50Hz: 1080P/720P(1~25fps) 50Hz: 720P/D1/CIF (1~25fps)
Functions	Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
	Remote Monitoring	UniApps Software / Mobile APP / IE Browser
	Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
	Network Protocol	UDP, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS
	Interface Protocol	ONVIF
	Audio Compression	G711A/U
	Smart Event	Intrusion detection
	PoE	Yes
	IR Distance	10 ~ 20 m
	Protection	IP67
Others	Power Supply	DC12V/PoE
	Power Consumption	<4.5W
	Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F); Humidity: less than 95 % (non-condensing)
	Dimensions (mm)	105mm*95mm

DIMENSIONS:

