

SK-DP5C3F-MS

5.0MP Full-Color Video & Audio PoE Network Camera



FEATURES :

- 5MP Network IR Fixed Dome
- H.265+/H.264 coding
- ICR auto switch, true day / night vision
- 3D DNR, WDR, HLC, BLC, smart IR, etc.
- 10~30m IR night view distance
- Built-in MIC & audio input
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by UniApps apps
- Intelligent analytics
- ONVIF Profile

DIMENSIONS:



SPECIFICATIONS

Camera	Model	SK-DP5C3F-MS
	Images Sensor	1/2.8" 5MP CMOS
	Illumination	Color : 0.01 lux @F1.2, AGC ON; 0 lux with IR
		Black : 0.001 lux @F1.2, AGC ON; 0 lux with IR
Image	Shutter	1/2s ~ 1 / 100000s
	Lens	4mm@F1.6
	Lens Mout	M12
	Focus	Fixed Lens
Functions	Video Compression	H. 265+
	Resolution	5MP (2560 × 1920), 1080P (1920 × 1080), 720P (1280 × 720), D1, 480× 240, CIF
	Main Stream	50Hz: 5 MP/3MP/1080P/720P(1~25fps)
	Sub Stream	50Hz: 720P/D1/CIF (1~25fps)
Others	Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
	Remote Monitoring	UniApps Software / Mobile APP / IE Browser
	Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
	Network Protocol	UDP, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS
	Interface Protocol	ONVIF
	Storage	Network remote storage; micro SD card storage
	Smart Event	Line crossing detection and Face detection
	PoE	Yes
Others	IR Distance	10 ~ 30 m
	Protection	IP67
	Power Supply	DC12V/PoE
	Power Consumption	<4.5W
	Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F); Humidity: less than 95 % (non-condensing)
Dimensions (mm)	170mm*85mm	